PRODUCT DATA SHEET



RACING P-V

RACING P-V are ropes with a Vectran® fibers (Liquid Crystal Polymer) core, covered by polyester jacket for extra UV and abrasion resistance.

Construciton: 12 strand Vectran® core. 16/24/32 strand polyester cover.

Features: Good abrasion and heat resistance, high load uses. The Vectran® core also offers low creep and minimal elongation. With treatment of UCS.

Application: Halyards. Control lines. After guys.



| | <u> 1989</u> 1997 | | | |
|---------|----------------------|----------|-----------|----------|
| X=1-Red | X=2-Yellow | X=3-Blue | X=4-Green | X=5-Grey |

| Reference | Diameter mm | Length m | Breaking Load kg |
|-----------|----------------|-------------|---------------------|
| 310112X | 4 | 200 | 730 |
| 310122X | 6 | 200 | 1730 |
| 310132X | 8 | 200 | 3720 |
| 310141X | 10 | 100 | 5400 |
| 310151X | 12 | 100 | 8000 |
| 310161X | 14 | 100 | 10300 |
| 310171X | 16 | 100 | 12700 |
| 310181X | 18 | 100 | 15750 |
| 310191X | 20 | 100 | 18800 |





HERZOG[®] FLECHTMASCHINEN 



Dyneema[®]

Vectran

an (l